



STREET ABBREVIATIONS

DRIVE	Dr
LANE	Ln
PATH	Path
STREET	St
AVENUE	Ave
ROAD	Rd
COURT	Ct
CIRCLE	Cir
BOULEVARD	Blvd
WAY	Way
TRAIL	Tr
CURVE	Curve
PARKWAY	Pkwy
UPPER	Upper
LOWER	Lower

SUFFIX ABBREVIATIONS

NORTH	N	(UPPERCASE)
WEST	W	(UPPERCASE)
SOUTH	S	(UPPERCASE)
TH	th	(LOWERCASE)
RD	rd	(LOWERCASE)
ND	nd	(LOWERCASE)

SIGN COLORS

PUBLIC STREETS - WHITE ON GREEN  
 PRIVATE STREETS - WHITE ON BROWN

HEIGHT OF SIGN - 9" MIN.  
 LENGTH OF SIGN - VARIABLE (36" MAX.)  
 UPPERCASE WHITE LETTERS - 6"  
 LOWERCASE WHITE LETTERS - 4.5"

NOTES:

1. ALL SIGNS SHALL BE .080 ALUMINUM (5052-H38 ALLOY) DOUBLE SIDED WITH 3M #4000 SERIES DG3 SHEETING, UNLESS OTHERWISE NOTED.
2. SIGN LEGEND SHALL BE APPLIED USING ANY 3M WARRANTIED MATCHED COMPONENT SYSTEM. THESE SYSTEMS INCLUDE SCREEN PRINTING, 3M APPROVED DIGITAL PROCESSING METHODS INCLUDING THERMAL TRANSFER PRINTING, APPLIED CUT-OUT COPY AND/OR APPLICATION OF 3M EC FILM. ANY SYSTEM USED WILL CARRY THE 3M WARRANTY IN THE 3M PRODUCT BULLETIN 4000.
3. ALL LEGENDS SHALL BE 6" FHWA C-SERIES LETTERING EXCEPT WHERE LIMITED BY SIGN LENGTH, THEN B-SERIES LETTERING SHALL BE USED. IF STILL LIMITED BY LENGTH, THEN 5" LETTERING AND/OR FORCED SPACING SHALL BE USED.
4. STANDARD COLOR SHALL BE WHITE LEGEND ON GREEN BACKGROUND EXCEPT WHERE INDICATED SPECIFICALLY TO BE WHITE/BROWN.
5. INSTALLATION SHALL BE IN COMPLIANCE WITH THE MOST CURRENT EDITION OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES & ALL CURRENT UPDATES TO THAT EDITION.
6. ALL EQUALS MUST BE APPROVED BY THE CITY ENGINEER PRIOR TO INSTALLATION.



STREET SIGN ON STREET LIGHT  
 FOR PUBLIC & PRIVATE STREETS

LAST REVISION:  
 DEC 2016

PLATE NO.  
 STR-21