

TYPICAL B & B TREE, SET LEVEL AND FACED TO PRIMARY VIEW

DOUBLE SHREDDED HARDWOOD BARK MULCH RING, 30" MINIMUM DIAMETER. FORM DISH AROUND TRUNK WITH NO MULCH IN CONTACT WITH TRUNK. MULCH THICKNESS 3"

LOOSEN, UNWRAP AND REMOVE BALLING MATERIALS FROM TRUNK AND TOP OF BALL. SLASH SIDES OF BURLAP AND BEND WIRE LOOPS INTO HOLE.

ROOT BALL, WRAPPED & LACED WITH NATURAL MATERIALS ONLY (NO PLASTIC). LOCATE ROOT FLARE AND SET BALL ON FIRM SOIL SO ROOT FLARE IS SLIGHTLY HIGHER THAN SURROUNDING GRADE IN A HOLE 2-3 TIMES BALL WIDTH WITH ROUGH, SLOPED SIDES.

BACKFILL WITH SOIL MIX AND FERTILIZER AS SPECIFIED. FIRMLY TAMP LOWER HALF TO STABILIZE BALL. WATER IN AS SPECIFIED.

TRUNK WRAP AS SPECIFIED.

SEE PLAN FOR ADJACENT SURFACES.

UNDISTURBED SUBGRADE.

THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING TREES IN A PLUMB POSITION THROUGHOUT THE GUARANTEE PERIOD.

2X - 3X



DECIDUOUS TREE PLANTING

LAST REVISION:
DEC 2019

PLATE NO.
GEN-7